

The most Economic Table-top Strapping Solution with Arch for strapping 8 – 15,5 mm PP-strap



Characteristics

Strapping qualities	Polypropylene (PP)
Strapping dimensions: widths thicknesses	8,0 – 15,5 mm (5/16 – 5/8") 0,55 – 0,75 mm (0.02 - 0.03")
Strapping tension, mechanical	adjustable, 100 – 700 N (22.5 - 157.4 lbf)
Sealing method	heat welding
Power supply	230V / 50Hz or 110V / 60Hz , 1 phase
Power consumption	1,2 kWh
Strapping speed	2,2 sec./cycle (approx. 27 strapping cycles/min.)
Dimensions	width 1.430 mm (56.3") length 620 mm (24.4") table height 810 mm (31.9")
Machine weight	220 kg (485 lb)
Max. package weight	100 kg (220.5 lb)
Min. package size	100W x 20H mm (3.94 x 0.79")
Arch size, standard	850W x 600H mm (33.5 x 23.6")
Desired ambient temperature	5 ~ 40°C (41 – 104°F)

Some Key Features and Benefits worth knowing

- User friendly, easy to operate;
 - Proven quality and reliability over the years;
 - External mechanical tension adjustment;
 - Short feed sensor and with Strap-end ejector;
 - Hinged stainless top plate, with safety switch;
 - Low maintenance requirements;
 - Easy strapping coil change and strap infeed;
 - Rigid castors with brake;
 - Competitively priced;
 - Foot pedal included;
 - Bundles and cartons can be strapped easy & quick;
 - CE certified;
- Multi user ready
 - Business reliability
 - Convenience
 - No need to remove strap residue.
 - Easy service access
 - Reliable and low service costs
 - Friendly working conditions
 - Mobile and stable work setup
 - Reduced payback period
 - Efficient and user friendly
 - Multi-purpose and efficient
 - Reassurance

Chart of the most frequent types PM308 Economic

Item. Nr.	Arch type (WxH)	Strap dimensions
45.4011	650x400mm / 25.6x15.75"	9mm / 3/8"
45.4012	650x400mm / 25.6x15.75"	12mm / 1/2"
45.4021	850x600mm / 33.5x23.6"	9mm / 3/8"
45.4022	850x600mm / 33.5x23.6"	12mm / 1/2"
45.4024	850x800mm / 33.5x31.5"	9mm / 3/8"
45.4025	850x800mm / 33.5x31.5"	12mm / 1/2"
45.4031	1.050x800mm / 41.3x31.5"	9mm / 3/8"
45.4032	1.050x800mm / 41.3x31.5"	12mm / 1/2"
45.4041	1.250x1.000mm / 49.2x39.4"	9mm / 3/8"
45.4042	1.250x1.000mm / 49.2x39.4"	12mm / 1/2"

Contact your FROMM representative for more options.

Most common applications

Strapping of small to medium quantities of:

- Boxes in various sizes
- Bundles of wood, profiles, tubes and more
- Large irregular packages
- Panels of wood, plastic, metal, etc.

