

Some Key Features and Benefits worth knowing

- Rotatable Smart control, panel with LCD screen, fitted to the arch; Easy to operate, Multi-user ready
- Proven quality and reliability; Operational reliability
- Electronic controlled tension force (soft or high) and cooling time (0-2 sec.); Consistent tension force and high seal efficiency
- Short feed sensor and strap-end ejector; No need to remove strap residue
- Auto strap ejector and strap refeed; Removes strap after strapping error and feeds again
- Lubrication free strapping head; Durability and reliability
- Hinged stainless top plate + safety switch; Easy service access
- Low maintenance requirements; Reliable and low service costs
- Automatic strap infeed at waist height; Friendly working conditions
- Rigid castors with brake; Mobile and stable work setup
- Fixed foot bar (front); Efficient and user-friendly operation
- System integration ready; Simple to integrate and communicate with modern automated systems
- Competitively priced; The most optimal performance and cost effective solution in its class.
- CE certified; Reassurance

Chart of the most frequent types PM313-12

H \ W	650mm 25.6"	850mm 33.5"	1.050mm 41.3"	1.250mm 49.2"	1.650mm 65"	1.850mm 72.8"	2.050mm 80.7"	2.250mm 88.6"
400mm / 15.7"		✓						
500mm / 19.7"	F		✓		✓		✓	
600mm / 23.6"		✓	✓	✓				✓
800mm / 31.5"		✓	✓	✓		✓		
1.000mm / 39.4"		✓	✓	✓				
1.200mm / 47.2"			✓	✓	✓			

F = Standard size.
Contact your FROMM representative for more options.

Most common applications for the 313 Series

(Automatic) High Speed Strapping of medium to large quantities

- Boxes, Print media, Mailing, Food, Logistics, Corrugated and more
- Bundles of wood, profiles, tubes, etc.

The 313 Series offers you some significant options

- Various top plates with Motorized transport belts (B) or rollers (R)
- Stainless steel frames
- Side seal versions (S)
- Pneumatic vertical package presses (P)
- Internal heating devices for cold / moister environments
- Extra foot bar at the rear
- Lower adjustable table height; 770 – 820 mm (30.3 – 32.3")

For further information, please refer to the relevant Data sheets or contact your FROMM representative.

